

SPECIFICATIONS:

- 1) TSO Compliance: TSO C129
Applicable Documents: RTCA DO-160C, DO-208
- 2) Operating Temperature Range: -55°C to +70°C
- 3) Humidity: 95% Non-Condensing.
- 4) Altitude Range: 0 to 55,000 ft.
- 5) Vibration: Cat. M and N.
- 6) Operational Shock: Rigid Mounting, 6G Operational
15G Crash Safety.
- 7) Current: 0.40 Amps typical.
- 8) Controls:
 - NAV/GPS: Alternate action switch.
 - OBS: Momentary switch.
- 9) Annunciations and colors:
 - NAV: white.
 - GPS: green.
 - INTG: amber.
 - TERM: green.
 - APR: green.
 - MSG: amber.
 - AUTO: white.
 - OBS: green.
 - WPT: amber.
- 10) Overall color shall be black.
- 11) Weight shall be 0.30 lbs.


25 PIN MALE
D-SUB CONNECTOR

INTG ANN.	20
ALT ANN.	6
APR ANN.	9
WPT ANN.	8
MSG ANN.	10
TERM ANN.	3
NAV ANN.	2
GPS ANN.	1
LAMP TEST	7
OBS MODE SELECT	12
AUTO ANN.	11
OBS ANN.	24
EXT. RELAY ENERGIZE	4
ILS ENERGIZE	14
14VDC POWER	13
NAV CIRCUIT BREAKER	15
GROUND	25
14V DIMMER IN	5

NOTE: Refer to manual number 8019358
for installation information.

Revisions				
ECO	Rev.	Description	Date	Approved
3246	A	0.125 was 0.08. Rearrange drawing	5/29/03	DDT/Sch

Logo and company name have been changed in title block only. No functional or technical changes have been made. Revision remains unchanged.



Vertical Mount

This document discloses proprietary information of Mid-Continent Instrument Co., Inc. It may be reproduced or disclosed only with written permission of Mid-Continent Instrument Co., Inc. and is not to be used in any way detrimental to the interests of Mid-Continent Instrument Co., Inc.

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES TOLERANCE: FRACTIONAL = ± 1/64 .XX = ± .020 .XXX = ± .010 .XXXX = ± .002 ANGULAR = ± 0.5° CONCENTRICITY: .005 TIR BREAK ALL SHARP EDGES THREADS PER MIL-5-7742 SURFACE ROUGHNESS <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>	DRAWN	S. Hoang	06/05/00		TITLE: ANNUNCIATION CONTROL UNIT	PART NUMBER: MD41-1414
	APPROVED	B. Barnes	06/05/00			
	TOP LEVEL ASSY:	8019440-1			SCALE: None	SHEET 1 of 1
	USED ON:					
	END ITEM:					
CODE IDENT. NO.:	59742					