

SPECIFICATIONS:

- 1) TSO Compliance: TSO C129
Applicable Documents: RTCA DO-160C, DO-208
- 2) Operating Temperature Range: -55°C to +70°C
- 3) Humidity: 95% Non-Condensing.
- 4) Altitude Range: 0 to 55,000 ft.
- 5) Vibration: Cat. M and N.
- 6) Operational Shock: Rigid Mounting, 6G Operational
15G Crash Safety.
- 7) Current: 0.30 Amps typical.
- 8) Controls:
 - NAV/GPS: Alternate action switch.
 - GPS/APR: Momentary switch.
 - GPS/SEQ: Alternate action switch.
- 9) Annunciations and colors:
 - NAV: white.
 - GPS: green.
 - MSG: amber.
 - ARM: white.
 - ACTV: green.
 - WPT: amber.
 - HOLD: amber.
 - AUTO: green.
- 10) Overall color shall be black.
- 11) Weight shall be 0.30 lbs.


25 PIN MALE
D-SUB CONNECTOR

AUTOPILOT ILS ENERGIZE	11
ACTV ANN	8
WPT ANN	9
MSG ANN	3
ARM ANN	4
NAV ANN	2
GPS ANN	1
LAMP TEST	7
GPS-SEQ HOLD	10
ILS ENERGIZE	15
EXTERNAL RELAY ENERGIZE	14
GPS APR ARM SELECT	6
NAV CIRCUIT BKR	12
28VDC POWER	13
GROUND	25
5V DIMMER IN	5

NOTE: Refer to manual number 7019813
for installation information.

Revisions				
ECO	Rev.	Description	Date	Approved
3236	A	0.125 was 0.08. Rearrange drawing. Spec. #7 was 0.4A	6/4/03	DDT/ScH

Logo and company name have been changed in title block only. No functional or technical changes have been made. Revision remains unchanged.



Vertical Mount

This document discloses proprietary information of Mid-Continent Instrument Co., Inc. It may be reproduced or disclosed only with written permission of Mid-Continent Instrument Co., Inc. and is not to be used in any way detrimental to the interests of Mid-Continent Instrument Co., Inc.

<p>UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES TOLERANCE: FRACTIONAL = ±1/64 .XX = ±.020 .XXX = ±.010 .XXXX = ±.002 ANGULAR = ±0.5° CONCENTRICITY: .005 TIR BREAK ALL SHARP EDGES THREADS PER MIL-S-7742</p>	DRAWN	S. Hoang	6/30/97		<p>TITLE: ANNUNCIATION CONTROL UNIT</p>	<p>PART NUMBER: MD41-1458(5V)</p>
	APPROVED	B. Barnes	6/30/97			
	TOP LEVEL ASSY:	9010422-6			<p>SCALE: None</p>	<p>SHEET 1 of 1</p>
	USED ON:					
SURFACE ROUGHNESS	CODE IDENT. NO.:	59742				