

SPECIFICATIONS:



- 1) TSO Compliance: TSO C129  
Applicable Documents: RTCA DO-160C, DO-208
- 2) Operating Temperature Range: -55°C to +70°C
- 3) Humidity: 95% Non-Condensing.
- 4) Altitude Range: 0 to 55,000 ft.
- 5) Vibration: Cat. M and N.
- 6) Operational Shock: Rigid Mounting, 6G Operational  
15G Crash Safety.
- 7) Current: 0.40 Amps typical.
- 8) Controls:
  - CDI: Momentary switch.
  - OBS: Momentary switch.
- 9) Annunciations and colors:
  - VLOC: white.
  - GPS: green.
  - MSG: amber.
  - WPT: amber.
  - TERM: green.
  - APR: green.
  - OBS: green.
  - AUTO: white.
  - INTG: amber.
- 10) Overall color shall be black.
- 11) Weight shall be 0.30 lbs.

25 PIN MALE  
D-SUB CONNECTOR

INTG ANN.	20
APR ANN.	9
WPT ANN.	8
MSG ANN.	10
TERM ANN.	3
VLOC ANN.	2
GPS ANN.	1
LAMP TEST	7
OBS MODE SELECT	12
OBS	24
CDI SOURCE SELECT	4
14VDC POWER	13
GROUND	25
14V DIMMER IN	5

Revisions				
ECO	Rev.	Description	Date	Approved
3200	A	Dimension 0.125 was 0.08. Revise drawing	5/28/03	DDT/SchH

Logo and company name have been changed in title block only. No functional or technical changes have been made. Revision remains unchanged.



Horizontal Mount

This document discloses proprietary information of Mid-Continent Instrument Co., Inc. It may be reproduced or disclosed only with written permission of Mid-Continent Instrument Co., Inc and is not to be used in any way detrimental to the interests of Mid-Continent Instrument Co., Inc.

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES TOLERANCE: FRACTIONAL = ±1/64 .XX = ±.020 .XXX = ±.010 .XXXX = ±.002 ANGULAR = ±0.5° CONCENTRICITY: .005 TIR BREAK ALL SHARP EDGES THREADS PER MIL-S-7742	DRAWN	S. Hoang	7/27/00		TITLE: ANNUNCIATION CONTROL UNIT	PART NUMBER: MD41-1464A
	APPROVED	B. Barnes	7/27/00			
		TOP LEVEL ASSY:	9010810-1			
		USED ON:				
	END ITEM:					
	SURFACE ROUGHNESS	CODE IDENT. NO.: 59742		SCALE: None	SHEET 1 of 1	